

SAFETY DATA SHEET

according to 1907/2006 EC, Article 31

Page 1 of 3

Dyne Test Solutions Type "A" – 33-43 Dynes/cm (mN/m)Revision 1
Revision date 3-Jan-2014**1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY**

Product name Dyne Test Solutions Type "A" – 33-43 Dynes/cm (mN/m)

Company Dyne Testing Limited
Newton House, 5 Parkside Court
Greenhough Road
Lichfield
Staffordshire
WS13 7FE United Kingdom
info@dynetesting.co.uk

Telephone +44 (0) 1543 411460

Fax +44 (0) 1543 415140

2. HAZARDS IDENTIFICATION

Main hazards Harmful by inhalation, in contact with skin and if swallowed. May impair fertility. May cause harm to the unborn child.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
2-Ethoxyethanol	20 - 90%	110-80-5	203-804-1	R10 Repr Cat 2; R60-61 Xn; R20/21/22
Formamide	10 - 80%	75-12-7	200-842-0	Repr Cat 2; R61

4. FIRST AID MEASURES

Skin contact Harmful if swallowed. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Eye contact May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation Harmful by inhalation. Move the exposed person to fresh air. Seek medical attention.

Ingestion Harmful if swallowed. Ingestion may cause nausea and vomiting. DO NOT INDUCE VOMITING. If swallowed, seek medical advice immediately and show this container or label.

5. FIRE FIGHTING MEASURES

Extinguishing media Use as appropriate: carbon dioxide (CO2).
Cool fire exposed containers with waterspray, dry chemical, foam.

Fire hazards

Protective equipment Wear self contained breathing apparatus and protective clothing.

Dyne Test Solutions Type "A" – 33-43 Dynes/cm (mN/m)

Revision

1

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Ensure adequate ventilation of the working area. Eliminate all sources of ignition. Wear suitable protective equipment.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Keep away from sources of ignition - No smoking. Adopt best Manual Handling considerations when handling, carrying and dispensing.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

2-Ethoxyethanol	WEL 8-hr limit ppm: 10 WEL 15 min limit ppm: -	WEL 8-hr limit mg/m ³ : 37 WEL 15 min limit mg/m ³ : -
Formamide	WEL 8-hr limit ppm: 20 WEL 15 min limit ppm: 30	WEL 8-hr limit mg/m ³ : 37 WEL 15 min limit mg/m ³ : 56

Engineering measures	Ensure adequate ventilation of the working area.
Occupational exposure controls	Keep away from food, drink and animal feedingstuffs.
Respiratory protection	Self-contained breathing apparatus.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	Approved safety goggles.
Protective equipment	Wear chemical protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Colour	Various.
Boiling point	135°C
Flash point	72 - 124°C

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Conditions to avoid	Heat, sparks and open flames. Air.
Materials to avoid	Oxidising agents. Copper and its alloys.
Hazardous decomposition products	Carbon oxides.

Dyne Test Solutions Type "A" – 33-43 Dynes/cm (mN/m)

Revision

1

11. TOXICOLOGICAL INFORMATION

Toxicological information

2-Ethoxyethanol
 Oral Rat LD50 = 2125 mg/kg Dermal
 Rabbit LD50 = 3300 mg/kg
 Inhalation Rat LC50/7 h = 2000 ppm

Formamide
 Oral Rat LD50 = 5577 mg/kg Dermal
 Rabbit LD50 = 1700 mg/kg
 Inhalation Rat LC50/6 h = 3900 ppm

Acute toxicity Harmful by inhalation, in contact with skin and if swallowed.
 Corrosivity May cause irritation to respiratory system. May cause irritation to eyes. May cause irritation to skin.
 Reproductive toxicity May impair fertility. May cause harm to the unborn child.

12. ECOLOGICAL INFORMATION

Mobility Soluble in water.

13. DISPOSAL CONSIDERATIONS

General information Dispose of in compliance with all local and national regulations.

14. TRANSPORT INFORMATION

Further information The product is not classified as dangerous for carriage.

15. REGULATORY INFORMATION

Symbols T - Toxic



Risk phrases R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed.
 R60 - May impair fertility.
 R61 - May cause harm to the unborn child.
 Safety phrases S36/37 - Wear suitable protective clothing and gloves.
 S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
 S53 - Avoid exposure - obtain special instructions before use.

16. OTHER INFORMATION

Text of risk phrases in Section 3. R10 - Flammable.
 R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed.
 R60 - May impair fertility.
 R61 - May cause harm to the unborn child.
 Further information The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.